



Products

[Rutile Titanium Dioxide Series](#)

[Anatase titanium Dioxide Series](#)

[- GA-100](#)

[- GA-102](#)

[- GA-120](#)

[Sulfuric Acid Series](#)

[Integrated Resource Series](#)

Anatase titanium Dioxide Series

Current Location: [Home](#) - [Products](#) - [Anatase titanium Dioxide Series](#)



Product Name: Anatase TiO2 GA-100

[Inquiry](#)

GA-100

GA-100 UNIVERSAL GRADE

KEY FEATURES:

Adopted unique technology, the product is characterized by excellent optical properties, good whiteness and opacity, and less abrasion to machine.

APPLICATIONS:

GA-100 is recommended for interior wall paint, interior decorative paint, primer, rubber, paper, leather, titanate-making, etc.

TYPICAL TECHNICAL DATA

TYPICAL PROPERTIES	PERFORMANCE	NATIONAL STANDARD OF TOP GRADE
TiO ₂ content, %	98.5, min	98
Color (compared with standard sample)	Obviously better than	Not lower than
Tint reducing power(compared with standard sample)	100, min	100
Oil absorption, (g/100g pigment)	22, max	26
Residue on 45µm, %	0.05, max	0.10
Water soluble objects, %	0.5, max	0.5
pH Value of aqueous suspension	6.5-8.0	6.5-8.0
Loss at 105°C, %	0.5, max	0.5

Standard sample: designated by the company

Previous: No Product

Next: Anatase TiO2 GA-102

Address: Tikon Industrial Park, Fuzhou City, Jiangxi Province, China Tel :0086-794-8355555 Fax :0086-794-8352555

Copyright Sansheng Group JiangXi Tikon Titanium CO., LTD.

[Links](#) ▼