



Products

[Rutile Titanium Dioxide Series](#)

[Anatase titanium Dioxide Series](#)

[- GA-100](#)

[- GA-102](#)

[- GA-120](#)

[Sulfuric Acid Series](#)

[Integrated Resource Series](#)

Anatase titanium Dioxide Series

Current Location: [Home](#) - [Products](#) - [Anatase titanium Dioxide Series](#)



Product Name: Anatase TiO2 GA-102

[Inquiry](#)

GA-102

GA-102 PLASTIC USE

KEY FEATURES:

Modified with special and advanced technology on the surface, the product has excellent compatibility with plastic solvent and easy to disperse. It is also characterized by low oil absorption, strong tinting strength and good whiteness. It is one of typical products of the

company.

APPLICATIONS:

GA-102 is particularly recommended for masterbatch, plastic and it can also be widely used in inks, special coatings and paper, etc.

TYPICAL TECHNICAL DATA

TYPICAL PROPERTIES	PERFORMANCE	NATIONAL STANDARD OF TOP GRADE
TiO ₂ content, %	98, min	98
Color(compared with standard sample)	Not lower than	Not lower than
Tint reducing power(compared with standard sample)	100, min	100
Oilabsorption,(g/100g pigment)	22, max	26
Residue on 45µm, %	0.1, max	0.1
Water soluble objects, %	0.5, max	0.5
pH Value of aqueous suspension	6.5-8.0	6.5-8.0
Specific resistance, Ω·m	20, min	20
Less at 105C, %	0.5, max	0.5

Standard sample:designated by the company

Previous: [Anatase TiO2 GA-100](#)

Next: [Anatase TiO2 GA-120](#)

Address: Tikon Industrial Park,Fuzhou City,Jiangxi Province,China Tel :0086-794-8355555 Fax :0086-794-8352555

Copyright Sansheng Group JiangXi Tikon Titanium CO., LTD.

[Links](#) ▼