

Marking

CAS-Number	7727-37-9
Characterization acc. ADR	UN 1066, Nitrogen, compressed, 2.2 Class 2, 1 A

Cylinder Marking

shoulder:
black

Essential properties

Colourless, odorless, asphyxiating gas, compressed, slightly lighter than air

Symbols of Risks

gas, compressed

Physical Properties

molecular weight:	28,0134 kg/kmol
gas density at 0°C and 1,013 bar:	1,250 kg/m ³
density ratio to air:	0,9671

For additional safety information see Material-/safety data sheet No. *-N2-089A

Valves / Manifolds

Valve connection	200bar: acc. to national standards 300 bar: ISO 5145 No. 1: W 30 x 2
Recommended Manifolds	Spectrotec

**Specifications / Forms of delivery**

		technical	4.0	
Composition				
N ₂	>	99,5	99,99	Vol.-%
Impurities				
H ₂ O	<	-	30	ppmv
O ₂	<	-	50	ppmv
Ar	<	-	30	ppmv
Cylinders / Contents				
F 10 200 bar		1,9	1,9	m ³
F 20 200 bar		3,8	3,8	m ³
F 20 300 bar		5,2	5,2	m ³
F 50 200 bar		9,6	9,6	m ³
F 50 300 bar		13,1	13,1	m ³
B 12* F 50 200 bar		114,7	114,7	m ³
B 12* F 50 300 bar		157,0	157,0	m ³

Marking

CAS-Number	7727-37-9
Characterization acc. ADR	UN 1066, Nitrogen, compressed, 2.2 Class 2, 1 A

Cylinder Marking

shoulder:
black

Essential properties

Colourless, odorless, asphyxiating gas, compressed, slightly lighter than air

Symbols of Risks

gas, compressed

For additional safety information see Material-/safety data sheet No. *-N2-089A

Description

Colourless, odorless, inert gas. In closed rooms the breathing air is displaced (danger of asphyxiation!); no warning symptoms!

Materials

Cylinders and valves: any usual materials

Seals: PTFE, PCTFE, PVDF, PA, PP, IIR, NBR, CR, FKM, Q, EPDM

Physical Properties	
molecular weight	28,0134 kg/kmol
Critical Point	
temperature	126,260 K
Pressure	34,10 bar
density	0,3140 kg/l
Triple Point	
temperature	63,150 K
Pressure	0,1246 bar
Boiling Point	
temperature	77,36 K; -196 °C
liquid density	0,8085 kg/l
evaporation heat	198,6 kJ/kg
vapour pressure at 20°C	
gas density at 0°C and 1,013 bar	1,250 kg/m ³
density ratio to air	0,9671
gas density at 15°C and 1 bar	1,1694 kg/m ³
Conversion Factor	
liquid at Ts to m ³ gas (15°C, 1 bar)	0,691
Virial Coefficient	
Bn at 0°C	-0,47*10 ⁻³ bar ⁻¹
B30 at 30°C	-0,17*10 ⁻³ bar ⁻¹
Gaseous State at 25°C and 1 bar	
specific heat capacity cp	1,040 kJ/kg K
thermal conductivity	256,6*10 ⁻⁴ W/m K
dynam. viscosity	17,9*10 ⁻⁶ Ns/m ²