



COLD TYPES


[BACK TO PRODUCTS](#)

COLD TYPES

Lion offers the most complete range of cold emulsion styrene butadiene rubber (eSBR) in the industry today. Their narrow molecular weight distribution makes them ideal for applications including tires, automotive, mechanical rubber goods, footwear, and/or general purpose applications in need of wear resistance and processing versatility. We offer a comprehensive selection of grades, the highest-quality products in the industry and the formulation support you need. We are committed to the continued production of quality SBR using modern quality control techniques and have designed products specifically for your industry.

[PACKAGING INFO](#)
[PRODUCT INFO](#)

COLD TYPES

| MSDS | TDS | GRADES | EMULSIFIER | STABILIZER | BOUND STYRENE (%) | MML 1+4 |
|-------------------|-------------------|--------|------------|------------|-------------------|---------|
| M | I | 1500 | RA | S | 23.5 | 51 |
| M | I | 1502 | MA | NS | 23.5 | 52 |
| M | I | 1502L | MA | NS | 23.5 | 41 |
| M | I | 1507 | MA | NS | 23.5 | 35 |

COLD OIL EXTENDED TYPES

| MSDS | TDS | GRADES | EMULSIFIER | STABILIZER | BOUND STYRENE (%) | MML 1+4 | OIL TYPE | OIL PARTS |
|-------------------|-------------------|--------|------------|------------|-------------------|---------|----------|-----------|
| M | I | 1712 | MA | S | 23.5 | 45 | Hi-AR | 37.5 |
| M | I | 1712L | MA | S | 23.5 | 35 | Hi-AR | 37.5 |
| M | I | 1763 | MA | S | 23.5 | 50 | NAPH | 37.5 |

| | | | | | | | | |
|----------|----------|-------|----|----|------|----|------|------|
| <u>M</u> | <u>I</u> | 1769 | MA | S | 40.0 | 50 | NAPH | 37.5 |
| <u>M</u> | <u>I</u> | 1778 | MA | NS | 23.5 | 52 | NAPH | 37.5 |
| <u>M</u> | <u>I</u> | 1732N | MA | S | 32.0 | 46 | NAPH | 32.5 |
| <u>M</u> | <u>I</u> | 1783 | MA | S | 23.5 | 52 | RAE | 37.5 |
| <u>M</u> | <u>I</u> | 1783L | MA | S | 23.5 | 45 | RAE | 37.5 |
| <u>M</u> | <u>I</u> | 1789 | MA | S | 40.0 | 52 | RAE | 37.5 |

©2015 Lion Elastomers | All rights reserved. | 